

Spacia® Collection | Wood

FINISH CODE: LVT-2  
DESCRIPTION: LUXURY VINYL TILE  
MANUFACTURER: MANNINGTON

| Style                              | Wood                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | 4mm Wood                                                                                                                                                          |
|------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Construction                       | Luxury Vinyl Tile<br>Non-ortho Phthalate<br>ASTM F1700 Class III, Type B                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Luxury Vinyl Tile<br>Non-ortho Phthalate<br>ASTM F1700 Class III, Type B                                                                                          |
| Classification                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                                                                                                   |
| Total Thickness                    | 0.098" (2.5 mm)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 0.1575" (4.0 mm)                                                                                                                                                  |
| Wear Layer Thickness               | 20 mil (0.51 mm)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 20 mil (0.51 mm)                                                                                                                                                  |
| Wear Layer                         | Quantum Guard Elite®                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Quantum Guard Elite®                                                                                                                                              |
| Edge Treatment                     | Micro-bevel                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Micro-bevel                                                                                                                                                       |
| Sizes                              | 6" x 36" (152.5 x 305 mm),<br>7.25" x 48" (184 x 1219 mm)<br>Sizes are style dependent; refer to Product Availability Chart                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 6" x 36" (152.5 x 457 mm),<br>7.25" x 48" (184 x 1219 mm)<br>Sizes are style dependent; refer to Product Availability Chart                                       |
| Colors                             | 68                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 68                                                                                                                                                                |
| Packaging                          | 6" x 36" - 30 pcs, 45 ft² (4.18 m²), 33.53 lbs (15.21 kg)<br>7.25" x 48" - 18 pcs, 43.5 ft² (4.04 m²), 32.41 lbs (14.70 kg)<br>Packaging may differ for QuickStix®                                                                                                                                                                                                                                                                                                                                                                                                                             | 6" x 36" - 12 pcs, 18 ft² (1.67 m²), 23.76 lbs (10.78 kg)<br>7.25" x 48" - 12 pcs, 29 ft² (2.694 m²), 38.28 lbs (17.36 kg)<br>Packaging may differ for QuickStix® |
| Adhesive                           | Porous & Non-porous Substrates:<br>V-88 / Amtico PSA Full Spread, Transitional Pressure Sensitive<br>MoistureLoc / Amtico RP-18 Full Spread, One Component<br>V-95 Full Spread, 2-Part Epoxy<br>XpressStep for LVT & Sheet Vinyl Full Coverage Spray<br>Note: Must use V-95, MoistureLoc, Amtico RP-18, QuickStix or XpressStep adhesive under hospital beds and heavy rolling load areas. In more abusive conditions such as areas subject to dragging force, direct sunlight or where topical moisture would be a concern, only V-95, MoistureLoc, Amtico RP-18 or QuickStix should be used. |                                                                                                                                                                   |
| QuickStix®                         | Available with QuickStix® pre-applied adhesive, reducing time and labor required to install the flooring. QuickStix® floors can be used immediately after installation, even in extreme moisture areas.                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                   |
| Installation Method                | All arrows in the same direction. Planks should have end joints offset by at least 6" and staggered to create a random appearance. Tiles should be installed block or staggered; when quarter turned, arrows should alternate.                                                                                                                                                                                                                                                                                                                                                                 |                                                                                                                                                                   |
| Testing                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                                                                                                   |
| HUD/FHA                            | Passes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                                                                   |
| Flexibility (ASTM F137)            | Passes - 1" Mandrel - No Crack/Break                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                                                                                                                                                   |
| Dimensional Stability (ASTM F2199) | Passes - Max 0.020 in/lin ft                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                                                                                                                                   |
| Squareness (ASTM F2055)            | Passes - Max 0.010"                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                                                                                                   |
| Static Load (ASTM F970 mod.)       | Passes - 2,000 PSI; Residual Indent ≤ 0.005"                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                                                                                                                                   |
| Residual Indentation (ASTM F1914)  | Passes - < 8% Avg / 10% Single Value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                                                                                                                                                   |
| Flooring Radiant Panel (ASTM E648) | Passes - Class 1; ≥ 0.45 watts/cm²                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                   |
| Smoke Density (ASTM E662)          | Passes - ≤ 450                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                                                                                                   |
| Slip Resistance (ASTM C1028)       | Passes - ≥ 0.5 Leather; 0.6 Rubber                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                   |
| Resistance to Light (ASTM F1515)   | Passes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                                                                   |
| Chemical Resistance (ASTM F925)    | Passes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                                                                   |
| Resistance to Heat (ASTM F1514)    | Passes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                                                                   |
| Environmental Data                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                                                                                                   |
| Rapidly Renewable Content          | Contains 2% rapidly renewable resource content                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                                                                                                   |
| Indoor Air Quality                 | FloorScore Certified; CDPH v1.2-2017                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                                                                                                                                                   |
| Product Declarations               | Third Party Verified EPD, HPD                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                                                                                                                                                   |
| Carbon Offset                      | 105% Cradle to Gate (A1 - A3), visit website for more information                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                                                                                                                                                   |
| LEED                               | May contribute to LEED credits:<br>Building Product Disclosure & Optimization - EPDs<br>Building Product Disclosure & Optimization - Sourcing Raw Materials<br>Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials                                                                                                                                                                                                                                                                                                                               |                                                                                                                                                                   |
| mindful MATERIALS<br>Manufacturing | Visit mindfulmaterials.com for current transparency information<br>Madison, GA (USA) - ISO 14001 EMS & ISO 9001 QMS Registered                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                                                                                                   |
| Warranty                           | Limited 15-Year Commercial Warranty<br>Limited 15-Year Quantum Guard Elite® Wear Warranty                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                                                                                                   |